

ANCHOR DIAMOND PRO™ STRAIGHT AND BEVELED UNITS
UNITS REQUIRED PER SQUARE METER OF WALL FACING
200mm HIGH UNITS

NUMBER OF UNITS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
HEIGHT (METERS)	0.2	0.40	0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.20	2.40	2.60	2.80	3.00
LENGTH (METERS)															
5	11	22	33	44	56	67	78	89	100	111	122	133	144	156	167
10	22	44	67	89	111	133	156	178	200	222	244	267	289	311	333
15	33	67	100	133	167	200	233	267	300	333	367	400	433	467	500
20	44	89	133	178	222	267	311	356	400	444	489	533	578	622	667
25	56	111	167	222	278	333	389	444	500	556	611	667	722	778	833
30	67	133	200	267	333	400	467	533	600	667	733	800	867	933	1000
35	78	156	233	311	389	467	544	622	700	778	856	933	1011	1089	1167
40	89	178	267	356	444	533	622	711	800	889	978	1067	1156	1244	1333
45	100	200	300	400	500	600	700	800	900	1000	1100	1200	1300	1400	1500
50	111	222	333	444	556	667	778	889	1000	1111	1222	1333	1444	1556	1667
55	122	244	367	489	611	733	856	978	1100	1222	1344	1467	1589	1711	1833
60	133	267	400	533	667	800	933	1067	1200	1333	1467	1600	1733	1867	2000
65	144	289	433	578	722	867	1011	1156	1300	1444	1589	1733	1878	2022	2167
70	156	311	467	622	778	933	1089	1244	1400	1556	1711	1867	2022	2178	2333
75	167	333	500	667	833	1000	1167	1333	1500	1667	1833	2000	2167	2333	2500
80	178	356	533	711	889	1067	1244	1422	1600	1778	1956	2133	2311	2489	2667
85	189	378	567	756	944	1133	1322	1511	1700	1889	2078	2267	2456	2644	2833
90	200	400	600	800	1000	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000
95	211	422	633	844	1056	1267	1478	1689	1900	2111	2322	2533	2744	2956	3167
100	222	444	667	889	1111	1333	1556	1778	2000	2222	2444	2667	2889	3111	3333

NOTE: For cost estimating purposes only. Professional engineering must be considered for proper design and reinforcement placement. Dimensions and construction tolerances vary from location to location. Contact your local supplier prior to placing your product order.